

# 1000V INSULATED SOCKETS

## 3/8" Drive Hex Head Sockets Metric - Long Length

Hex Size	Part No.	Overall Length, mm	Bit Length, mm
4mm	MTW4L-I	98	70
5mm	MTW5L-I	98	70
6mm	MTW6L-I	100	70
7mm	MTW7L-I	100	70
8mm	MTW8L-I	100	70
10mm	MTW10L-I	100	70

Individually insulated and tested to ASTM F1505 Standards. ⚠



## 3/8" Drive Torx® Head Sockets - Standard Length

Torx® Size	Part No.	Overall Length, in.	Tamper Resistant Bit Part No.
T6	T606-I	2.125	—
T7	T607-I	2.125	T607T-I
T8	T608-I	2.125	T608T-I
T9	T609-I	2.125	T609T-I
T10	T610-I	2.125	T610T-I
T15	T615-I	2.125	T615T-I
T20	T620-I	2.125	T620T-I
T25	T625-I	2.125	T625T-I
T27	T627-I	2.125	T627T-I
T30	T630-I	2.125	T630T-I
T40	T640-I	2.125	T640T-I
T45	T645-I	2.125	T645T-I
T50	T650-I	2.125	T650T-I
T55	T655-I	2.125	—

Torx® is a trademark of Camcar Division of Textron, Inc.

Individually insulated and tested to ASTM F1505 Standards. ⚠



## 3/8" Drive Phillips® Head Sockets - Standard Length

Phillips® Size	Part No.	Overall Length, in.	Bit Length, in.
No.1	TP1-I	1.93	0.75
No.2	TP2-I	1.93	0.75
No.3	TP3-I	1.93	0.75
No.4	TP4-I	1.93	0.75

Phillips® is a trademark of Phillips Screw Company.

Individually insulated and tested to ASTM F1505 Standards. ⚠



**Safety Tip:** If you are able to see the yellow safety insulated under-layer showing through the orange layer, the tool is no longer safe to use and should be replaced.