183



Part No.	Drive	Imperial Range	Incr.	Newton Meter Range	Incr.	No. of Teeth	Head Style	Accuracy
*MFR1000HD	1″	200 - 1000 ft./lbs.	5	305 - 1322 Nm	6.8	30	Fixed-head	± 4% CW ± 6% CCW
**MF2000	1″	300 - 2000 ft./lbs.	10	N/A	N/A	30	Fixed - non ratcheting head	$\pm$ 4% CW $\pm$ 6% CCW

\*NOTE: MFR1000HD is supplied with one extension handle and includes a metal storage box.



Part No.	Drive	Imperial Range	Incr.	Newton Meter Range	Incr.	No. of Teeth	Head Style	Accuracy
81250	1/4″	30 - 250 in/lbs.	1	4 - 28.8 Nm	0.11	36	Fixed-head	$\pm$ 4% CW $\pm$ 6% CCW

## Features:

- Individually serialized with matching factory certificate of calibration traceable to N.I.S.T.
- Accuracy noted above is from 20% to 100% of full scale
- Fast, accurate and easy to set in any industrial workplace
- · Easy-to-read scales
- Rugged aluminum knurled handles
- · Quick release button for faster socket retention and removal • Meets or exceeds ASME B107.14-2004, ISO 6789 standards
- Includes plastic storage case.